



DATA INQUIRY SHEET

6535 SERIES

PACKAGED HEAT PUMP

Specifications By Model Number	Stage 1 & 2	Stage 1 Only
Electrical Rating	115 VAC, 60 HZ, 1 Phase	
Cooling Full Load AMP's at A.R.I. Standard Condition	Compressor - System 1 & 2 - 9.0 each Fan Motor - Outdoor Hi - 3.3 Fan Motor - Indoor Blower Hi - 3.41 Total - 24.7	System 1 - 8.9 Outdoor Lo - 2.62 Indoor Blower Lo - 3.12 Total - 14.64
Running Watts: (Cooling) A.R.I. Standard Condition (80 F. DB/67 F. WB Indoor, 95 F. DB Outdoor at 103.5 VAC)	2784	1650
Running Watts: (Heating) A.R.I. Standard Condition (70 F. Indoor, 47 F. DB/43 F. WB Outdoor at 115 VAC)	2563	1521
Compressor Locked Rotor Amps	54.0	
Compressor Ohm Ratings (approx.) C = Common, S = Start, R = Run	(C-S) 4.42 $\pm$ 5%	(C-R) .63 $\pm$ 5%
Electronic Thermostat Set Temperature Range	40 F. To 90 F.	
Metering Device	Biflow Restrictor	
Refrigerant Charge	30.75 oz. each system	30.75 oz.
Evaporator Air Delivery (CFM)	600 @ .4 External Static	
Installed Weight (pounds)	200	

